



Probes with connection head

- Aluminium alloy/Noryl/Stainless steel head
- Stainless steel, heat resisting steel or mineral insulated sheath, Alard coating...
- Wire mounting : single pair (2, 3 or 4 wires) or multipair (4 or 6 wires)

Pt 100 / Pt 1000 / NTC Thermocouple (K, J, T, N...)





Piping probe

Precision probes for industrial fields

One need: One customized probe! CONTACT US!



Interchangeable probe system



ALU / Noryl / Stainless steel head 🚁 🖚 🧼 🕌

Wire probes

- Industry requirements
- Food-industry requirements
- Precision probes
- Wire mounting single pair (2, 3 or 4 wires) or multipair (4 or 6 wires)

Pt 100 / Pt 1000 / NTC Thermocouple (K, J, T, N...)

Standard or **Custom-Made**



Cable and outputs

PVC / Silicone / Teflon® / Glass silk cable Stainless steel hose (with or without shielding) Pt 100 / Pt 1000 / NTC / Thermocouple

2, 3 or 4 wires outputs (Single or multipair wire



BS head Pt 100 / 0-10 V / 4-20 mA output...












- From -50 to +400°C • Length from 1000 to 2000mm
- Stainless steel protection sheath





- Miniature or standard panel sockets
- Connector panels
- Coiled thermocouple extension leads



• Converters / transmitters (4-20 mA / 0-10 V / 2 wires



• Power supply Class 2 (Alternating or direct current)

00.00


- Adjustable ring
- Adjustable compression fitting

One need: One customized probe!

CONTACT US!

- Mounting brackets
- Wall fixing support











ssembling components, compression fittings, mounting rackets, thermowell, miniature or standard panels sockets...



- With ot without display
- Duct mount, remote or ambient-end probe
- Quick and easy mounting











